

****CEILING CASSETTE MUST BE PURCHASED/USED WITH CASSETTE DISCHARGE GRILLE,
WHICH COMES SEPARATELY****

Model Number		TM12HKDI	TM18HKDI	TM24HKDI
Type		Cassette		
SYSTEM PERFORMANCE				
Voltage/Phase/Hertz		208-230V/1/60Hz	208-230V/1/60Hz	208-230V/1/60Hz
Cooling Capacity	Btu/h	12,000	14,400	22,800
Heating Capacity	Btu/h	13,000	16,000	27,400
Airflow (min/max)	CFM	265/353	265/353	500/694
Sounds Level (min/max)	dB(A)	42/46	42/46	45/49
Dehumidification	pt/hr	3.0	3.8	5.3
DIMENSIONS				
Cabinet Dimensions (WxHxD)	in	22.4 x 9.1 x 22.4	22.4 x 9.1 x 22.4	33.1 x 10.2 x 33.1
Package Dimensions (LxWxH)	in	33.5x28.8x12.8	33.5x28.8x12.8	37.9x37.9x12.8
Weight (Net/Gross)	lbs	40/51	40/51	62/77
INSTALLATION				
Line Connection Size (Liquid - Gas/Suction)	in	1/4 - 3/8	1/4 - 1/2	3/8 - 5/8
ACCESSORY (REQUIRED)				
Discharge Grille		Small	Small	Large
Grille Dimensions (WxHxD)	in	25.6 x 2.0 x 25.6	25.6 x 2.0 x 25.6	37.4 x 2.4 x 37.4
Weight (Net/Gross)	lbs	5.5/8.0	5.5/8.0	14.3/22.0