### Save PDF

### Back to List

**ccASHP** 

**TOSOT FLEXX High-efficiency Series** Central Air Conditioning Heat Pump (HP) Singlezone Ducted, Centrally Ducted AHRI Cert #: 209843759 Outdoor Unit Model #: TU60-24WADU Indoor Model #: TUD60-24AH2ADU Maximum Heating Capacity (Btu/h) @5°F: 41,000

Rated Heating Capacity (Btu/h) @47°F: 54,000

Rated Cooling Capacity (Btu/h) @95°F: **54,000** Performance Specs

Basic View 1


Advanced Data -Sizing for Heating

Brand	TOSOT	Heating /	Outdoor	Indoor				
Series	FLEXX High-	Cooling	Dry Bulb	Dry Bulb	Unit	Min	Rated	Мах
	efficiency Series	Cooling	95°F	80°F	Btu/h	15,300	54,000	54,000
Ducting Configuration	Singlezone Ducted,				kW	1.43	5.4	5.4
	Centrally Ducted				COP	3.14	2.93	2.93
AHRI Certificate #	209843759	Cooling	82°F	80°F	Btu/h	19,100	-	56,000
Outdoor Unit Model #	TU60-24WADU				kW	1.13	-	4.48
ndoor Model #	TUD60-24AH2ADU				COP	4.95	-	3.66
ndoor Unit Type		Heating	47°F	70°F	Btu/h	16,000	54,000	54,000
Furnace Model #		C			, kW	1.1	5.1	5.1
EER	10.5				COP	4.26	3.1	3.1
SEER	17	Heating	17°F	70°F	Btu/h	18,300	36,000	36,000
HSPF (Region IV)	10	rieating			kW	2.15	4.39	4.39
ER2	10							
SEER2	15.8		505	7005	COP	2.49	2.4	2.4
ISPF2 (Region IV)	9	Heating	5°F	70°F	Btu/h	19,000	41,000	41,000
HSPF2 (Region V)	7				kW	2.91	6.67	6.67
ENERGY STAR V6.1	✓				COP	1.91	1.8	1.8
ENERGY STAR V6.1 Cold		Heating	-22°F	70°F	Btu/h	18,600	-	24,300
Climate	✓				kW	4.52	-	6.19
NERGY STAR V5.0					COP	1.21	-	1.15
ederal Tax Credit Eligibility North								
Federal Tax Credit								

**Eligibility South** 

66%
75%
75%
✓
R410A
LIGA. Conodo

# Heating/Cooling Capacity Graph



## Pan Heater

Туре	Integrated
Input Power (W)	160
Operation	When outdoor ambient temperature is below 33.8°F or the unit is running defrost,the heater will turn on.

## Additional Heat Pump Images

Related Products		