

Outdoor Unit Model		TM48H2O	TM56H2O
Number of Zones		8	9
Compressor Type		DC Inverter-Driven Rotary	
Energy Star		No	No
Coil Type		Copper Aluminum with Anti-Corrosion Coating	
Cooling Capacity (min-max)	Btu/h	47,800 (3,412 - 54,592)	52900 (3,412 - 61,416)
SEER/EER *		16.0/9.56	16.0/9.45
Heating Capacity (min-max)	Btu/h	54,600 (4,094 - 59,369)	61400 (4,094 - 63,122)
HSPF/COP		8.2	8.2
Cooling Temperature Range	F	5 - 118	5 - 118
Heating Temperature Range	F	-4 - 75	-4 - 75
Sound Level	dB(A)	55	57
Total Line Length	ft	443	476
Length to farthest Indoor Unit	ft	230	230
Elevation (ODU above IDU)	ft	98	98
Line Connection Size - (Liquid - Gas/Suction)	inch	3/8 - 5/8	3/8 - 5/8
Voltage/Phase/Hertz		208-230V/1/60Hz	208-230V/1/60Hz
MCA (Rated Current - Cooling)	amp	23	25
Unit dimension (WxDxH)	in	35x15x53	35x15x53
Package Dimension (LxWxH)	in	39x18x55	39x18x55
Outdoor Unit Weight (Net/Gross)	lbs	256/279	256/279
Limited Warranty		7 Years on Compressor and 5 Years on Parts	