



SUBMITTAL DATA

TM09D6FLI
9000 BTU/H Floor Ceiling Heat Pump System

Job Name	Location	Date
Purchaser	Engineer	
Submmited to	For	
Unit Designation	Schedule No.	



YBE1FB5F



TM09D6FLI



XE72-44/E

GENERAL FEATURES

- Quiet Operation and Multi-Speed Fan
- Floor Stand or Ceiling Mount
- Multi-Directional Air Flow
- WirelessRemotewithLCD Display Included
- XE72-44/E Wired Controller Included
- Low Ambient Cooling and Heating
- (Indoor and Outdoor) Copper Tube / Aluminum Fin
- Blue Colored Fin - 500 Hrs Salt Spray Tested
- New R32 Refrigerant with Refrigerant Sensor

SPECIFICATIONS, FEATURES & FUNCTION SUMMARY

INDOOR MODEL			TM09D6FLI
System Type			HEAT PUMP
SYSTEM PERFORMANCE			
Cooling	Min - Max	Btu/h	900 - 14,100
	Capacity @95°F	Btu/h	9,100
Heating	Min - Max	Btu/h	900 - 15,500
	Capacity @47°F	Btu/h	10,500
	Capacity @17°F	Btu/h	6,700
	Capacity Max @5°F	Btu/h	10,000
SEER2			25.0
EER2			14.2
HSPF2			9.6
COP @5°F			1.95
Cooling Temperature Range		°F	-20 - 122
Heating Temperature Range		°F	-22 - 86
Refrigerant Type			R32
INDOOR UNIT			TM09D6FLI
Air flow (Min-Max)		CFM	247 - 412
Sound Pressure Level (Min - Max)		dB(A)	26 - 38
Dehumidification		pt/hr	1.69
External Dimensions (L x D x H)		in	34-1/4 x 9-1/4 x 26-3/16
Package Dimension (L x W x H)		in	40-11/16 x 30-5/16 x 11-13/16
Net Weight		lbs	55.1
Gross Weight		lbs	66.2
REFRIGERANT PIPING			
Refrigerant Charge - R410A		oz	30
Additional Charge		oz/ft	0.2
Line Set Sized by Indoor Unit (Liquid - Gas)		in	1/4 - 3/8
Line Set Size (Liquid - Gas) - Flared Connections		in	1/4 - 3/8
Pre-Charge Length		ft	25
Pipe Length (Min - Max)		ft	10 - 66
Max. Pipe Elevation		ft	40
ELECTRICAL			
Power Supply		208-230V / 1Ph / 60Hz (Powered by the Outdoor Unit)	
Voltage Range (Min - Max)		VAC	187 - 253
Rated Current - Cooling		A	4.73
Rated Current - Heating		A	6
MCA		A	10
MOCP		A	15
Suggested Breaker Size		A	10
Main Power Wire Size		AWG	Per Local Code
Interconnecting Wire Size		AWG	14 / 4

FEATURES & FUNCTIONS SUMMARY

SYSTEM FEATURES

Inverter Type	G20 with Field Oriented control (FOC)
---------------	---------------------------------------

Ultra Low Frequency Torque Control	Yes
------------------------------------	-----

Power Factor Correction	Yes
-------------------------	-----

Compressor Type - Inverter	High Efficiency Rotary
----------------------------	------------------------

Basepan With Electric Heater	Yes
------------------------------	-----

Indoor & Outdoor Fin Coating (Blue Fin)	Yes
---	-----

Intelligent Defrosting	Yes
------------------------	-----

Intelligent Preheating	Yes
------------------------	-----

Low Voltage Startup	Yes
---------------------	-----

Memory/Power Failure Recovery	Yes
-------------------------------	-----

Self Diagnosis	Yes
----------------	-----

Wired Controller Interface	Yes
----------------------------	-----

WiFi Included	No
---------------	----

Indoor Fan Type	Centrifugal
-----------------	-------------

Multi Fan Speeds	4 Speeds
------------------	----------

Indoor Unit Display	Yes
---------------------	-----

Auxiliary Electrical Heater	No
-----------------------------	----

Ventilation (Outdoor Air)	Yes
---------------------------	-----

REMOTE CONTROLLER FUNCTIONS

Auto Mode	Yes
-----------	-----

Auto Fan	Yes
----------	-----

Auto Swing (Horizontal Auto Swing)	No
------------------------------------	----

Auto Swing - 180° (Vertical Auto Swing)	Yes
---	-----

Clock	Yes
-------	-----

Dry Mode	Yes
----------	-----

Dry Anti-Mildew (X-Fan) Mode	Yes
------------------------------	-----

Energy Saving Mode	Yes
--------------------	-----

Dirty Filter Alert	No
--------------------	----

Fan Speed Control (7 Speeds)	Yes
------------------------------	-----

I Feel Function	Yes
-----------------	-----

Privacy Lock	Yes
--------------	-----

Quiet Mode	Yes
------------	-----

Room Temperature Display	No
--------------------------	----

Sleep Mode	Yes
------------	-----

3 Sleep Mode Options	Yes
----------------------	-----

Timer Mode	Yes
------------	-----

Turbo Mode	Yes
------------	-----

Display On/Off Control	Yes
------------------------	-----

Freeze Guard Mode	Yes
-------------------	-----

Power Failure Mode	Yes
--------------------	-----

NOTE:



Please check the Multi-zone submittals for Non-Ducted or Mixed Performance table.

DIMENSIONS

INDOOR UNIT

Unit: inch

TM09D6FLI	
DIMENSIONS	
A	34 1/4
B	9 1/4
C	31 31/32
D	12 33/64
H	26 3/16



CLEARANCES

INDOOR UNIT

Minimum clearance

DIMENSIONS	
A	60
B	12
C	39
D	6
E	90

Unit: inch

