



## SUBMITTAL DATA

TM18D6FLI  
18000 BTU/H Floor Ceiling Heat Pump System

Job Name	Location	Date
Purchaser	Engineer	
Submmited to	For	
Unit Designation	Schedule No.	



YBE1FB5F



TM18D6FLI



XE72-44/E

### GENERAL FEATURES

- Quiet Operation and Multi-Speed Fan
- Floor Stand or Ceiling Mount
- Multi-Directional Air Flow
- WirelessRemotewithLCD Display Included
- XE72-44/E Wired Controller Included
- Low Ambient Cooling and Heating
- (Indoor and Outdoor) Copper Tube / Aluminum Fin
- Blue Colored Fin - 500 Hrs Salt Spray Tested
- New R32 Refrigerant with Refrigerant Sensor

## SPECIFICATIONS, FEATURES & FUNCTION SUMMARY

INDOOR MODEL			TM18D6FLI
System Type			HEAT PUMP
SYSTEM PERFORMANCE			
Cooling	Min - Max	Btu/h	5,100 - 23,200
	Capacity @95°F	Btu/h	18,000
	Min - Max	Btu/h	5,800 - 23,500
Heating	Capacity @47°F	Btu/h	18,000
	Capacity @17°F	Btu/h	10,200
	Capacity Max @5°F	Btu/h	15,800
SEER2			21.5
EER2			12.8
HSPF2			9.5
COP @5°F			1.90
Cooling Temperature Range		°F	-20 - 122
Heating Temperature Range		°F	-22 - 86
Refrigerant Type			R32
INDOOR UNIT			TM18D6FLI
Air flow (Min-Max)		CFM	241 - 400
Sound Pressure Level (Min - Max)		dB(A)	26 - 38
Dehumidification		pt/hr	3.8
External Dimensions (L x D x H)		in	34-1/4 x 9-1/4 x 26-3/16
Package Dimension (L x W x H)		in	40-11/16 x 30-5/16 x 11-13/16
Net Weight		lbs	56.2
Gross Weight		lbs	67.3
REFRIGERANT PIPING			
Refrigerant Charge - R410A		oz	40.6
Additional Charge		oz/ft	0.2
Line Set Sized by Indoor Unit (Liquid - Gas)		in	1/4 - 1/2
Line Set Size (Liquid - Gas) - Flared Connections		in	1/4 - 1/2
Pre-Charge Length		ft	25
Pipe Length (Min - Max)		ft	10 - 131
Max. Pipe Elevation		ft	82
ELECTRICAL			
Power Supply			208-230V / 1Ph / 60Hz (Powered by the Outdoor Unit)
Voltage Range (Min - Max)		VAC	187 - 253
Rated Current - Cooling		A	11.5
Rated Current - Heating		A	11.5
MCA		A	16
MOCP		A	20
Suggested Breaker Size		A	20
Main Power Wire Size		AWG	Per Local Code
Interconnecting Wire Size		AWG	14 / 4

## FEATURES & FUNCTIONS SUMMARY

### SYSTEM FEATURES

Inverter Type	G20 with Field Oriented control (FOC)
Ultra Low Frequency Torque Control	Yes
Power Factor Correction	Yes
Compressor Type - Inverter	High Efficiency Rotary
Basepan With Electric Heater	Yes
Indoor & Outdoor Fin Coating (Blue Fin)	Yes
Intelligent Defrosting	Yes
Intelligent Preheating	Yes
Low Voltage Startup	Yes
Memory/Power Failure Recovery	Yes
Self Diagnosis	Yes
Wired Controller Interface	Yes
WiFi Included	No
Indoor Fan Type	Centrifugal
Multi Fan Speeds	4 Speeds
Indoor Unit Display	Yes
Auxiliary Electrical Heater	No
Ventilation (Outdoor Air)	Yes

### REMOTE CONTROLLER FUNCTIONS

Auto Mode	Yes
Auto Fan	Yes
Auto Swing (Horizontal Auto Swing)	No
Auto Swing - 180° (Vertical Auto Swing)	Yes
Clock	Yes
Dry Mode	Yes
Dry Anti-Mildew (X-Fan) Mode	Yes
Energy Saving Mode	Yes
Dirty Filter Alert	No
Fan Speed Control (7 Speeds)	Yes
I Feel Function	Yes
Privacy Lock	Yes
Quiet Mode	Yes
Room Temperature Display	No
Sleep Mode	Yes
3 Sleep Mode Options	Yes
Timer Mode	Yes
Turbo Mode	Yes
Display On/Off Control	Yes
Freeze Guard Mode	Yes
Power Failure Mode	Yes

### NOTE:



Please check the Multi-zone submittals for Non-Ducted or Mixed Performance table.

DIMENSIONS

INDOOR UNIT

Unit: inch

TM18D6FLI	
DIMENSIONS	
A	34 1/4
B	9 1/4
C	31 31/32
D	12 33/64
H	26 3/16



CLEARANCES

INDOOR UNIT

Minimum clearance

DIMENSIONS	
A	60
B	12
C	39
D	6
E	90

Unit: inch

